



SAFETY DATA SHEET (Aerosol) Wheel Protector

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME (Aerosol) Wheel Protector
 PRODUCT NO. A 83
 SUPPLIER Autosmart International Ltd
 Lynn Lane,
 Shenstone, nr Lichfield
 Staffordshire. WS14 0DH
 England
 www.autosmartinternational.com
 Tel: +44 (0) 1543 481616 (09:00 - 17:00)
 Fax: +44 (0) 1543 481549 (09:00 - 17:00)
 info@autosmartinternational.com
 EMERGENCY TELEPHONE Mob: +44 (0) 7808 971321 (24hrs)
 Tel: +44 (0) 1543 481616 (09:00 - 17:00)
 Fax: +44 (0) 1543 481549 (09:00 - 17:00)

2 HAZARDS IDENTIFICATION

Extremely flammable. Repeated exposure may cause skin dryness or cracking. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION F+;R12. R52/53, R66.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTANE	203-448-7	106-97-8	30-60%	F+;R12
CALCINED KAOLIN CLAY		1332-58-7	< 1%	-
PARAFFIN WAX	232-315-6	8002-74-2	< 1%	-
PROPANE	200-827-9	74-98-6	10-30%	F+;R12
SOLVENT NAPHTHA	265-191-7	64742-88-7	10-30%	Xn;R65. N;R51/53. R10,R66.
XYLENE	215-535-7	1330-20-7	< 1%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

(Aerosol) Wheel Protector

SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Be aware of danger of explosion.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire. HIGHLY FLAMMABLE!

SPECIFIC HAZARDS

Carbon monoxide (CO). Carbon dioxide (CO2). Nitrous gases (NOx).

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

For personal protection, see section 8.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Eliminate all sources of ignition.

STORAGE PRECAUTIONS

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
CALCINED KAOLIN CLAY	WEL		2 mg/m3			
PARAFFIN WAX	WEL		2 mg/m3		6 mg/m3	
PROPANE		Asphyxiating Asphyxiating	Asphyxiating	Asphyxiating Asphyxiating	Asphyxiating	
SOLVENT NAPTHA	WEL		600 mg/m3			
XYLENE	WEL	50 ppm	220 mg/m3	100 ppm	441 mg/m3	Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

(Aerosol) Wheel Protector

HAND PROTECTION

Use protective gloves made of: Rubber, neoprene or PVC. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact. Provide eyewash station.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol Liquid		
COLOUR	Brown		
ODOUR	Strong. Solvent.		
SOLUBILITY	Soluble in Organic solvents.		
FLASH POINT (°C)	~ -2 CC (Closed cup).	VOLATILE ORGANIC COMPOUND (VOC)	588 g/litre

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions. Avoid: Heat, sparks, flames. Shocks and physical damage.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

INHALATION

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Drowsiness, dizziness, disorientation, vertigo.

INGESTION

May cause discomfort if swallowed. Drowsiness, dizziness, disorientation, vertigo.

SKIN CONTACT

May cause defatting of the skin, but is not an irritant.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

HEALTH WARNINGS

Because of quantity and composition, the health hazard is small.

ROUTE OF ENTRY

Inhalation. Ingestion.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Do not puncture or incinerate even when empty. Empty aerosols should be recycled where facilities exist. Full or part full aerosols should be disposed of as hazardous waste in accordance with local authority requirements.

(Aerosol) Wheel Protector

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground.

14 TRANSPORT INFORMATION

UK ROAD CLASS	2.1		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	#
ADR CLASS NO.	2.1	ADR CLASS	Class 2: Gases
ADR PACK GROUP	#	ADR LABEL NO.	2.1
CEFIC TEC(R) NO.	20G5F	RID CLASS NO.	2.1
RID PACK GROUP	#	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PAGE NO.	93 (vol 2)
IMDG PACK GR.	#	EMS	F-D, S-U
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1950	AIR CLASS	2.1
AIR PACK GR.	#		

15 REGULATORY INFORMATION

LABELLING



Extremely Flammable

CONTAINS

SOLVENT NAPHTHA

RISK PHRASES

R12	Extremely flammable.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.

SAFETY PHRASES

S2	Keep out of the reach of children
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

GENERAL INFORMATION

Only trained personnel should use this material.

REVISION DATE 05/09/2008

REV. NO./REPL. SDS GENERATED 2

(Aerosol) Wheel Protector

SDS NO. 1

RISK PHRASES IN FULL

R10	Flammable.
R12	Extremely flammable.
R20/21	Harmful by inhalation and in contact with skin.
R38	Irritating to skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.