Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: CO/TECH

Supplier's address: Product Compliance & Sustainability Department, Clas Ohlsons väg, SE-79385

Insjön, SE

Model identifier: 368666000 (SDS723v0sc827840)

_	•			
Ivpe	ot	light	source	

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type	-		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

Product parameters

Parameter		Value	Parameter	Value
General product parameters:				
	nption in on- 00 h), rounded st integer	6	Energy efficiency class	D
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	800 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27004000
On-mode pow pressed in W	ver (P _{on}), ex-	5,6	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	-
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	48	Spectral power dis-	See image
sions without	Width	90	tribution in the	in last page
separate con-	Depth	90		

trol gear, light- ing control parts and non- lighting con- trol parts, if any (millime- tre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,458		
		nates (x and y)	0,410		
Parameters for directional light	sources:				
Peak luminous intensity (cd)	-	Beam angle in de-			
		grees, or the range			
		of beam angles that			
		can be set			
Parameters for LED and OLED light sources:					
R9 colour rendering index value	-	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable;

(b)'-': not applicable;