Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: North Light

Supplier's address: Product Compliance & Sustainability Department , Clas Ohlsons väg, SE-79385 Insjön, SE

Model identifier: 361322000 (EU0301.2)

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	G4				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	2	Energy efficiency class	G		
Useful luminous flux (ϕ use), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	100 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode power (P _{on}), expressed in W	1,2	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer Height	30	Spectral power	See image		
dimensions Width	9	distribution in the	in last page		

withoutDepthseparateControl gear,lightingControl partsandnon-lightingControl parts,ifany(millimetre)	9	range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	Yes	lf yes, equivalent power (W)	11		
		Chromaticity	0,458		
		coordinates (x and y)	0,410		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	1	Survival factor	0,90		
the lumen maintenance factor	0,93				

(a)'-' : not applicable;

(b)'-' : not applicable;

