

36-3425



	$\varnothing \text{ mm}^2$	A	Width mm	Pcs
Red	0,5-1,65	10	6,3	10
Blue	1,04-2,63	15	6,3	10



	$\varnothing \text{ mm}^2$	A	Width mm	Pcs
Red	0,5-1,65	10	6,3	5
Blue	1,04-2,63	15	6,3	5



	$\varnothing \text{ mm}^2$	A	Width mm	Pcs
Red	0,5-1,65	10	6,3	10
Blue	1,04-2,63	15	6,3	10
Yellow	2,63-6,64	24	6,3	5



	$\varnothing \text{ mm}^2$	A	Pcs
Red	0,5-1,65	19	10
Blue	1,04-2,63	27	10
Yellow	2,63-6,64	48	5



	$\varnothing \text{ mm}^2$	A	Pcs
Red	0,5-1,65	10	10
Blue	1,04-2,63	15	10



	$\varnothing \text{ mm}^2$	A	Pcs
Red	0,5-1,65	10	10
Blue	1,04-2,63	15	10



	$\varnothing \text{ mm}^2$	A	Pcs
Red	0,5-1,65	19	5
Blue	1,04-2,63	27	5

Working temperature:

-25-75 °C

Material:

Tinned copper/Tinned brass

Insulation:

Polyvinyl chloride (PVC)

Voltage max:

300 V