Product Information Sheet

separate con-

trol gear, light-

control

ing

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLLOAILD REGOI	LATION (LO) 2013/2	ots with regard to energ	gy labelling of light	
Supplier's name	or trade mark:	LEDVANCE			
Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany					
Model identifie	r: AC32135				
Type of light so	urce:				
Lighting technology used:		LED	Non-directional or directional:	NDLS	
Light source cap-type		R7s			
(or other electri	c interface)				
Mains or non-mains:		MLS	Connected light source (CLS):	No	
Colour-tuneable	e light source:	No	Envelope:	-	
High luminance		No			
Anti-glare shield	d:	No	Dimmable:	No	
Product parameters					
Parameter		Value	Parameter	Value	
		General product p		I	
- .	nption in on- 00 h), rounded st integer	12	Energy efficiency class	E	
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone errow cone (90º)	1 521 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700	
On-mode power (P _{on}), expressed in W		12,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	118	Spectral power dis-	See image	
sions without	Width	20	tribution in the	in last page	

20

range 250 nm to 800

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	100			
		Chromaticity coordinates (x and y)	0,458 0,410			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	1	Survival factor	0,90			
the lumen maintenance factor	0,70					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-': not applicable; (b)'-': not applicable;

