

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Clas Ohlson

**Supplier's address:** Product Compliance & Sustainability Department , Clas Ohlsons väg, SE-79385 Insjön, SE

**Model identifier:** 369957001 (LG232012-CSv00-E14-2700K)

**Type of light source:**

|   |     |                                 |      |
|---|-----|---------------------------------|------|
| Lighting technology used:                           | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | E14 |                                 |      |
| Mains or non-mains:                                 | MLS | Connected light source (CLS):   | No   |
| Colour-tunable light source:                        | No  | Envelope:                       | -    |
| High luminance light source:                        | No  |                                 |      |
| Anti-glare shield:                                  | No  | Dimmable:                       | No   |

## Product parameters

| Parameter  | Value                    | Parameter  | Value   |
|--|--------------------------|--|---|
| <b>General product parameters:</b>   |                          |  |   |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 2                        | Energy efficiency class  | A   |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 252 in Sphere (360°)     | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700   |
| On-mode power ( $P_{on}$ ), expressed in W   | 1,2                      | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00  |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                        | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80  |
| Outer dimensions without separate control gear, light-   | Height<br>Width<br>Depth | 79<br>45<br>45   | Spectral power distribution in the range 250 nm to 800 nm, at full-load<br>See image in last page |

|   |                  |                                       |                |
|---|------------------|---------------------------------------|----------------|
| ing control parts and non-lighting control parts, if any (millimetre)   |                  |                                       |                |
| Claim of equivalent power <sup>(a)</sup>  | -                | If yes, equivalent power (W)          | -              |
|   |                  | Chromaticity coordinates (x and y)    | 0,470<br>0,429 |
| <b>Parameters for LED and OLED light sources:</b>   |                  |                                       |                |
| R9 colour rendering index value   | 0                | Survival factor                       | 0,90           |
| the lumen maintenance factor  | 0,96             |                                       |                |
| <b>Parameters for LED and OLED mains light sources:</b>   |                  |                                       |                |
| displacement factor ( $\cos \phi 1$ )   | 0,50             | Colour consistency in McAdam ellipses | 6              |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | - <sup>(b)</sup> | If yes then replacement claim (W)     | -              |
| Flicker metric (Pst LM)   | 1,0              | Stroboscopic effect metric (SVM)      | 0,4            |

(a) - : not applicable;

(b) - : not applicable;