## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Sources  |               |                         |  |              |  |  |
|--|---------------|-------------------------|--|--------------|--|--|
| Supplier's name or trade mark: Clas Ohlson   |               |                         |  |              |  |  |
| Supplier's address: -  |               |                         |  |              |  |  |
| Model identifier: 366841000 (LDS-F1G45-2-E27-F)  |               |                         |  |              |  |  |
| Type of light so   | urce:         |                         |  |              |  |  |
| Lighting techno  | logy used:    | LED                     | Non-directional or directional:  | NDLS         |  |  |
| Light source cap-type  |               | E27                     |  |              |  |  |
| (or other electri  | ic interface) |                         |  |              |  |  |
| Mains or non-mains:  |               | MLS                     | Connected light source (CLS):  | No           |  |  |
| Colour-tuneable light source:  |               | No                      | Envelope:  | -            |  |  |
| High luminance light source:   |               | No                      |  |              |  |  |
| Anti-glare shield:   |               | No                      | Dimmable:  | Yes          |  |  |
| Product parameters   |               |                         |  |              |  |  |
| Parameter  |               | Value                   | Parameter  | Value        |  |  |
| General product parameters:  |               |                         |  |              |  |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |               | 2                       | Energy efficiency class  | G            |  |  |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |               | 136 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700        |  |  |
| On-mode power (P <sub>on</sub> ), ex-<br>pressed in W  |               | 2,0                     | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |  |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |               | -                       | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 90           |  |  |
| Outer dimen-   | Height        | 72                      | Spectral power dis-  | See image    |  |  |
| sions without  | Width         | 45                      | tribution in the   | in last page |  |  |
| separate con-<br>trol gear, light-<br>ing control  | Depth         | 45                      | range 250 nm to 800<br>nm, at full-load  |              |  |  |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre)  |                      |  |                |
|---|----------------------|--|----------------|
| Claim of equivalent power <sup>(a)</sup>  | Yes                  | If yes, equivalent power (W)           | 15             |
|   |                      | Chromaticity coordinates (x and y)     | 0,463<br>0,420 |
| Parameters for LED and OLED li  | ght sources:         |  |                |
| R9 colour rendering index value   | 30                   | Survival factor                        | 0,90           |
| the lumen maintenance factor  | 0,70                 |  |                |
| Parameters for LED and OLED n   | nains light sources: |  |                |
| displacement factor (cos φ1)  | -                    | Colour consistency in McAdam ellipses  | -              |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. |                      | If yes then replace-<br>ment claim (W) | <del>-</del>   |
| Flicker metric (Pst LM)   | 1,0                  | Stroboscopic effect metric (SVM)       | 0,4            |

(a)'-': not applicable; (b)'-': not applicable;