Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: DELTACO	
--	--

Supplier's address: SweDeltaco, Glasfibergatan 8, 12545 Älvsjö Stockholm, SE

Model identifier: SH-LE27RGB

_	•			
Tyna	Ot.	lioht	sour	CD.
IVDC	O.	IIGIIL	30ui	LC.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Troduct parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
<u> </u>	nption in on- 00 h), rounded st integer	9	Energy efficiency class	F	
dicating if it refe a sphere (360°)	s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º)	806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500	
On-mode pow pressed in W	ver (P _{on}), ex-	9,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	-	
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	0,48	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	81	
Outer dimen-	Height	112	Spectral power dis-	See image	
sions without	Width	60	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	60	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	60	
		Chromaticity coordinates (x and y)	0,457 0,419	
Parameters for LED and OLED li	ght sources:			
R9 colour rendering index value	-100	Survival factor	0,90	
the lumen maintenance factor	0,93			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,95	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1	

(a)'-': not applicable; (b)'-': not applicable;

